

CCI (931I) SERIES

Commercial Ceiling Heater




Technical Specifications:

- Temp Range: 40°–90°F
- CFM: 150
- Grille Gauge: 14

Applications:

- Hallways
- Lobbies
- Entryways
- Restrooms
- Detention Environments



Beige

Standard Construction Features:

Choose these fan-forced ceiling heaters anywhere it makes sense to keep your heating solution out of the way and out of reach. A comfort solution for lobbies, restrooms and educational environments.

- Multiple mounting options: Recessed, Surface or T-Bar
- Accommodates pneumatic/electric or low voltage controls commonly used with BMS Systems
- Built in power on/off switch for safe, simple installation and maintenance
- When using wall thermostat, separate thermostat wiring is required
- Automatic fan delay eliminates cold drafts on start-up and discharges residual heat from the heater body during shut down
- Heavy duty 14-gauge louvered front cover grille with tamper-resistant screws provide added security and durability
- Remote thermostats available; i.e. M600S can be used to control two units, pending amperage requirements are met.

CCI (931I) SERIES

Commercial Ceiling Heater

Models & Specifications:

ELECTRICAL DATA						
CATALOG NO.	VOLTS	PHASE	WATTS	AMPS	BTU/HR	SHIP WT.
9311F-F1500-N	120	1	1500	12.5	5120	23 lbs
9311F-F3007-N	277	1	3000/1500	10.8/5.4	10239/5120	23 lbs
9311F-F4008-N	208	1	4000/2000	19.2/9.8	13652/6826	23 lbs
9311F-F4004-N	240	1	4000/2000	16.7/14.4	13652/10239	23 lbs
	208	1	3000/1500		10239/5120	
9311F-F4007-N	277	1	4000/2000	14.4/12.5	13652/10239	23 lbs
	240	1	3000/1500		10239/5120	
9311F-F4804-N	240/208	1	4800/3600	20.0/17.3	16382/12287	23 lbs
9311F-F4807-N	277/240	1	4800/3600	17.3/15.0	16382/12287	23 lbs
9311F-F48483-N	480	3	4800	5.8	16382	23 lbs
9311F-F48483L-N	480	3	4800	5.8	16382	23 lbs
9311F-F3003-N	347	3	3000	8.6	10239	23 lbs
EFF3006	600	3	3000	5	10239	23 lbs
9311F-F4003-N	347	3	4000	11.5	13652	23 lbs
9311F-F4006-N	600	3	4000	6.7	13652	23 lbs
9311F-F4803-N	347	3	4800	13.8	16382	23 lbs
9311F-F4806-N	600	3	4800	8	16382	23 lbs

NOTE: Factory-wired for highest wattage, field-convertible to lower wattages. Orders above 7500' sea level require special order

Optional Accessories:

CATALOG NO.	DESCRIPTION	SHIP WT.
FIF-FSM-N	Surface Mounting Sleeve - Beige	6 lbs
FIR-FR2-Z (24V)	Time delay relay, 45-60 seconds to close when energized; Uses remote 24V or 120V power source	1 lbs
FIR-FR12-Z (120V)		
FIF-FTBF-N	T-Bar Frame Kit	4.5 lbs
FIT-FT1-Z	Single Pole T-Stat. (Field Installed)	1 lbs
FIT-FFT2-Z	Double Pole Thermostat. (Field Installed)	2 lbs
FIR-FTR4-Z	208/240V Primary Transformer 24V Relay	1 lbs
FIR-FTR7-Z	277V Primary 24V Sec. Transformer Relay	1 lbs

Dimensions and Clearances:

