

WLI (934I) SERIES

Fan-Forced Small Wall Heater




Technical Specifications:

- Temp Range: 45°–90°F
- CFM: 50
- Grille Gauge: 20

Applications:

- Bedrooms
- Kitchens
- Bathrooms
- Basements
- Offices
- Hallways
- Lobbies
- Waiting Rooms



White



Stainless Steel

Standard Construction Features:

- Ideally suited for recessed shallow wall mount applications such as manufactured homes
- Fast response open coil element for instantaneous heat and low maintenance
- Dual Protection: Thermal cutout with indicator light and one-time thermal fuse
- Field wiring compartment for ease of installation
- Built-in double-pole thermostat on all units
- Ceiling-mount units (1,000 watt units) and surface-mount accessories available
- Internal thermostat can be bi-passed and a external thermostat can be used. See manual for more information.

WLI (934I) SERIES

Fan-Forced Small Wall Heater

Models & Specifications:

ELECTRICAL DATA							
CATALOG NO.	VOLTS	PHASE	WATTAGE	AMPS	BTU/HR.	CEILING MOUNT	SHIP WT.
934IW-D1012-C*	120	1	1000	8.3	3410	Yes	12 lbs
934IW-D1512-W	120	1	1500	12.5	5115	No	12 lbs
934IW-D2024-W	240/208	1	2000/1500	8.3/7.2	6820/5115	No	12 lbs
934IW-D1012-W	120	1	1000	8.3	3410	Yes	12 lbs
934IW-D1024-C*	240/208	1	1000/750	4.2/3.6	3410/2557	Yes	12 lbs
934IW-D1024-W	240/208	1	1000/750	4.2/3.6	3410/2557	Yes	12 lbs

NOTE: Units available in built in or wall mounted thermostats. *Stainless Steel models.

Optional Accessories:

CATALOG NO.	DESCRIPTION	SHIP WT.
WIF-DSM-W	White Surface Mounting Frame	3 lbs
WIF-DSMC-C	Stainless Steel Surface Mounting Frame	3 lbs
WIC-DFCW-W	Front Cover — White	2 lbs
WIC-DFCC-C	Front Cover — Stainless Steel	2 lbs

Dimensions and Clearances:

